

High Speed Colour Duplex Scanner

fi-6670/A



11 8 images-per-minute scanning speed
@200 dpi B&W or greyscale

200 page automatic document feeder

Ultrasonic multi-feed detection

Kofax VRS® Professional included

Hardware accelerated VRS available

1 year exchange warranty

ADOBE® ACROBAT® 8 STANDARD



FUJITSU

THE POSSIBILITIES ARE INFINITE

fi-6670



Speedy

The 89 ppm / 178 ipm capable (Letter, Landscape, 200 dpi) fi-6670A and fi-6670 are the fastest scanners in their class. Image processing is made easy, with the ability to continuously scan 200 sheet documents containing paper of different weights, quality and sizes. The fi-6670 and fi-6670A can even scan paper up to 3 m long enabling digitization of electrocardiograms, instrumental data readings and other long documents.

Kofax Hardware VRS Board

The fi-6670A comes loaded with a Kofax Hardware VRS board that optimizes image quality on the most difficult of documents. By performing advanced image enhancements in the scanner rather than in the computer, a higher scanning speed is obtained – up to 178 images per minute at 200 dpi.

"Intelligent" functions/design for efficient operation

The ability to adapt to different paper types is the key to a true batch document scanner. The fi-6670 and fi-6670A come loaded with features allowing the scanners to work autonomously.

• Intelligent multi-feed function

The intelligent multi-feed function simplifies pre-scanning preparation and improves efficiency by identifying documents that tend to trigger false multi-feed alerts, such as documents with photos or sticky notes attached.

• Straight paper path

The straight paper path virtually eliminates paper jams while permitting a greater diversity of paper types.

• Dust resistant sealed optical units

The sealed optical units in the fi-6670 and fi-6670A ensure that image quality is maintained, even in the most demanding environments such as factories and warehouses.

ScandAll PRO image capture software

The bundled ScandAll PRO image capture software supports advanced functions such as:

• Automatic job separation

The bar code based automatic job separation function of the fi-6670 and fi-6670A allows the scanner operator to have scanned documents automatically named or routed to their appropriate folders.

• Microsoft® Office SharePoint® Server linkability

ScandAll PRO enables these scanners to seamlessly link with Microsoft® Office SharePoint® Server

Kofax VRS (VirtualReScan) Professional

The fi-6670 comes bundled with Kofax Software VRS Professional Workgroup, the fi-6670A comes bundled with Kofax Hardware VRS Professional Production.



TECHNICAL SPECIFICATIONS

Scanner type		ADF (Automatic Document Feeder)
Scanning modes		Simplex / Duplex Colour / Greyscale / Monochrome
Image sensor type		2x colour CCDs (Charged Coupled Device)
Light source		4x white cold cathode discharge lamp (2x front, 2x back)
Scanning range	<i>Minimum</i>	2.0" x 3.0" (52 x 74 mm)
	<i>Maximum</i>	11" x 17" (279 x 431 mm) / Up to 120" (3048 mm) in long document mode ⁹
Paper weight (Thickness)		Letter size or smaller: 8.3 to 55.6 lb. Over Letter size: 13.8 to 55.6 lb. Business cards: 33.8 to 55.6 lb. Supports ISO7810 (non-embossed) card feedability
Scanning speed² (Letter, Landscape)		89 ppm / 178 ipm (200 dpi colour ³ , greyscale ³ , or monochrome) 79 ppm / 158 ipm (300 dpi colour ³ , greyscale ³ , or monochrome) 148 ipm with Hardware VRS board (300 dpi colour ³)
Scanning speed² (Letter, Portrait)		73 ppm / 145 ipm (200 dpi colour ³ , greyscale ³ , or monochrome) 62 ppm / 124 ipm (300 dpi colour ³ , greyscale ³ , or monochrome)
Paper chute capacity⁵		Max. 200 sheets (Letter 20 lb.); Active loadable ADF
Background		Black and white (auto-switching)
Optical resolution		600 dpi
Output resolution⁴		50 to 600 dpi (adjustable by 1 dpi increments)
Output format	<i>Colour</i>	24 bit (8 bit and 4 bit with driver)
	<i>Greyscale</i>	8 bit (4 bit with driver)
	<i>Monochrome</i>	1 bit
AD converter		10 bit
Drivers		TWAIN and ISIS™
Interfaces⁵⁺⁶	<i>fi-6670/fi-6670A</i>	Ultra SCSI / USB 2.0 (selectable)
	<i>fi-6670A only</i>	Ultra Wide SCSI / USB 2.0 (selectable)
Connector shape	<i>Ultra SCSI</i>	Shield type 50-pin
	<i>Ultra Wide SCSI</i>	Shield type 68-pin
	<i>USB</i>	B Type
SCSI terminator		Built-in
Output mode (Half-tone)		Dither / Error diffusion
Voltage		AC 100 to 240 V +/-10%, 50/60 Hz
Power	<i>Operating</i>	216 watts or less
	<i>Sleep mode</i>	Less than 6 watts
Operational environment	<i>Temperature</i>	5°C to 35°C (42°F to 95°F)
	<i>Relative humidity</i>	20% to 80% (non-condensing)
Dimensions⁷ (W x D x H)		641 x 432 x 300 mm (25.2" x 17.0" x 11.8")
Weight		17 kg (37.5 lb.)
Environmental compatibility		EnergyStar® and RoHS ⁸
Other	<i>Multi-feed detection</i>	Standard; Ultrasonic multi-feed detection sensor

OPTIONS

Post imprinter (FI-667PR) PA03576-D101	Assists document management by printing numbers, Roman characters and codes on original documents after they have been scanned.
Kofax Hardware VRS Board (FI-677CGA) PA03576-K001	This Fujitsu fi-Series scanner hardware option works with Kofax VRS to further speed up image processing. It comes bundled with the fi-6670A.

CONSUMABLES

ScanAid kit CG01000-527601	Up to 750,000 sheets or 1 year. The kit includes 3 pick rollers, 3 brake rollers, and 1 cleaning kit.
--------------------------------------	--

BUNDLED ITEMS

Hardware	ADF paper chute, Stacker, AC cable, USB cable, Setup DVD-ROM, Adobe® Acrobat® DVD-ROM, Getting Started, QuickScan™ Pro brochure, Operator panel overlay
Software	TWAIN and ISIS™ drivers, ScandAll PRO, Adobe® Acrobat®, QuickScan™ Pro (Trial), Image Processing Software Option, Kofax VRS Professional

WARRANTY

	1 year exchange warranty. Visit www.fujitsu.ca/warranty/scanner/ for more details.
--	---

SERVICE OPTIONS

Post warranty maintenance coverage	Provides post warranty remedial maintenance.
---	--

¹ CGA board does not support Microsoft Windows 64 bit versions

² Actual scanning speeds are affected by data transmission and software processing times

³ JPEG compressed figures

⁴ Maximum capacity varies, depending upon paper weight

⁵ You cannot use both SCSI and USB 2.0/1.1 interfaces at the same time

⁶ You cannot connect multiple computers to the scanner using each type of interface cables at the same time

⁷ Excluding the ADF paper chute and stacker

⁸ PFLU Limited, a Fujitsu company, has determined that this product meets RoHS requirements (2005/95/EC)

⁹ The fi-6670/fi-6670A is capable of scanning the following documents that exceed A3 in length:

- Documents not exceeding 863 mm (34") in length at resolutions between 201 dpi and 400 dpi, and documents not exceeding 3048 mm (120") in length at resolutions between 50 dpi and 200 dpi with TWAIN and ISIS™ (Long paper scanning does not support resolutions that exceed 400 dpi.)
- Documents not exceeding 863 mm (34") in length at resolutions of 300 dpi or lower with VRS

Fujitsu and the Fujitsu logo are registered trademarks of Fujitsu Limited. Adobe, Acrobat, Adobe PDF logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Kofax, VirtualReScan, Adrenaline and the "VRS VirtualReScan" logo are registered trademarks of Kofax Image Products. All the other trademarks mentioned herein are the property of their respective owners. Specifications are subject to change without notice.
© 2008 Fujitsu Canada, Inc. All rights reserved. FCI-09.16.2008-E



MultiCIM Technologies Inc.
14 Westminster N, suite 306C
Montreal West, QC, CANADA H4X 1Y8
T : (514) 633-6401 or 1 (877) MULTICIM
F : (514) 633-6495
sales@exadox.com



THE POSSIBILITIES ARE INFINITE