

fi-6800

A high speed *Colour Duplex Scanner*

*260 images per minute scanning speed
at 300dpi in Colour or B&W*

*Kofax VRS 4 Professional
hardware image processing*

*Intelligent ultrasonic
multi-feed function*

*Automatic Image
Quality Checker*

*500-page feeder with
automatic stacker*

One year on-site warranty



MultiCIM Technologies Inc.
14 Westminster N, suite 306C
Montreal West, QC, CANADA H4X 1Y8
T : (514) 633-6401 or 1 (877) MULTICIM
F : (514) 633-6495
sales@exadox.com

FUJITSU

fi-6800



Fast scanning

The fi-6800 offers fast 130ppm / 260ipm scanning at 300 dpi in colour or in B&W — ideal for OCR applications.

The versatile ADF on the fi-6800 can accommodate documents from business cards up to 12"x17" or larger of various textures and thicknesses.

New functions that boost automation and efficiency

In addition to supporting Scan to File, Scan to Print, Scan to Email, Scan to FTP and Scan to SharePoint, the included ScandAll Pro software provides advanced functions such as barcode or patchcode separation and Automatic Image Quality Checker.



Barcode or patchcode separation provides hands free sorting and saving of documents by reading the barcodes or patchcodes that are included on the document or on separator sheets.

Automatic Image Quality Checker detects image irregularities such as multi-feeds or damaged pages and alerts the operator by highlighting the affected pages in red or yellow respectively — allowing the operator to quickly assess if any documents require further review without interrupting the batch.

Less maintenance required

The fi-6800 has been designed to minimize the amount of preventative maintenance required to maintain peak efficiency.

- Feed rollers that resist the build-up of residue even when scanning NCR (carbonless) paper
- Sealed optical units prevent dust from depositing on the lenses or mirrors
- Electrically charged scanning glass repels paper dust

Paper protection

Advanced paper movement monitoring allows the fi-6800 to tackle feed problems before they happen — protecting your documents from damage.

Kofax VRS Professional for Production

- Kofax VRS Professional for Production included
- VRS verification and adjustment features generate clean images every time
- Easy to use, automated functions eliminate the need for skilled scanner operators



Technical Specifications

Scanner Type	ADF (Automatic Document Feeder) + Manual Feed
Scanning Modes	Simplex/Duplex; Colour / Grayscale / B&W
Image Sensor Types	Colour CCD (Charge-coupled Device)x2 (Front x1, Back x1)
Light Source	White LED Array
Document size	Max: 12 x 17 in Min: 2 x 3 in
Paper weight	11 to 56 lbs (5.4 to 56 lbs for A4 to A5 paper)
Scanning Speed*1 (Letter Landscape)*1 (Colour*2 / Grayscale*2 / B&W)	TWAIN / ISIS: 130ppm / 260 ipm at 300 dpi VRS: 130ppm / 250 ipm at 300 dpi
Paper Chute Capacity	500 sheets (Letter size, 20lb)*3
Background Colours	White , Black (auto-Selecting)
Optical Resolution	600 dpi
Output Resolution*4	50 to 600 dpi (adjustable by 1 dpi increments) (100/150/200/240/300/400 dpi) *With VRS board
Output Format	Colour: 24 bit, 8 bit (8 bit and 4 bit with driver) Grayscale: 8 bit (4 bit with driver) B&W: 1 bit
Interfaces*5	TWAIN / ISIS: Ultra SCSI (50 pin), USB2.0 VRS : Ultra Wide SCSI (68 pin), USB 2.0
Output Mode (half-tone)	Dither / Error Diffusion
Voltage Range	AC 100 to 240V ± 10%
Power	Operating: 200W or less (Sleep Mode: less than 5.3W)
Operational Environment	Temperature: 15 to 35 °C (59 to 95 °F) Relative Humidity: 20 to 80% (Non-condensing)
Dimensions*7 (WxDxH)	460 x 430 x 310mm (18.1 x 16.9 x 12.2 in)
Weight	32kg
Environmental Compatibility*8	Energy Star ® and RoHS
Others	Ultrasonic multi-feed detection (3 sensors) Long paper scanning up to 3048 mm (120 in)

Options

Post Imprinter (Front) (fi-680PRF)	PA03575-D201	The imprinter option enables users to print information on original documents for document management purposes. While the fi-680PRF (post imprinter) prints information on the front of documents, the fi-680PRB (post imprinter) prints information on the reverse-side of documents after they have been scanned. Although both the fi-680PRF and the fi-680PRB may be attached to the same scanner unit, both imprinters cannot be used simultaneously.
Post Imprinter (Back) (fi-680PRB)	PA03575-D203	

Consumables

Pick Roller	PA03575-K011	Lifetime: Every 600,000 sheets or one year These rollers feed documents into the scanner
Separator Roller	PA03575-K012	Lifetime: Every 600,000 sheets or one year This roller separates documents
Brake Roller	PA03575-K013	Lifetime: Every 600,000 sheets or one year This roller separates documents
Print Cartridge	CA00050-0262	Lifetime: 4,000,000 characters fi-680PRF and fi-680PRB print head

Bundled Items

	USB cable, Adobe Acrobat 9.0 Standard, ScandAll Pro ISIS/TWAIN drivers, Kofax VRS 4.0 Professional
--	--

Warranty

1 year on-site	For more details visit: www.fujitsu.ca/warranty/scanner/
----------------	--

1) Actual scanning speeds are affected by data transmission and software processing times 2) JPEG compressed figures 3) Maximum capacity varies, depending upon paper weight 4) Excluding the ADF paper chute and stacker 5) Pfu Limited, a Fujitsu company, has determined that this product meets RoHS requirements (2005/95). Fujitsu and the Fujitsu logo are registered trademarks of Fujitsu Limited. Adobe, Acrobat, Adobe PDF logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. All the other trademarks mentioned herein are the property of their respective owners. Specifications are subject to change without notice. © 2009 Fujitsu Canada, Inc. All rights reserved. FCI-0109